



Oxbo International
100 Bean Street
Clear Lake, WI
54005

tel 715.263.2112
800.628.6196

For your local dealer,
visit: www.oxbo.com
or scan the QR code
to learn more about
Oxbo mergers



Pull-type Mergers



Specifications	Model 918	Model 1416	Model 1800
Dimensions			
Transport width:	12ft (3.66m)	14ft 2in (4.32m)	14ft 2in (4.32m)
Working width:	22ft 5in (6.83m)	29ft 9in (6.07m)	33ft 3in (6.0m)
Length:	20ft (6.1m)	19ft 8in (5.99m)	19ft 8in (5.99m)
Transport height:	9ft 1in (2.77m)	13ft 6in (4.12m)	14ft (4.27m)
Working height:	7ft 1in (2.16m)	5ft 9in (1.75m)	5ft 9in (1.75m)
Tractor Requirements			
Tractor size:	50hp minimum	100hp minimum	
3-point hitch:		Cat II, III-N, or III	
PTO:	540 or 1000 RPM	1000 RPM (choices of 1.375in, 21 spline; or 1.75in, 20 spline)	
General			
Conveyor belt width:	35in (0.89m)	35in (0.89m)	
Max transport speed:	20mph (32km/hr)		
Operating speed:	2-12mph (3-19km/hr)		
Rear wheel tire size:	6.70 x 15	11 L x 15	
Gauge wheel tire size:	16.5 x 6.5, 8 ply		

918, 1416, & 1800



Every Oxbo merger is backed by local dealers and Oxbo's commitment to **superior customer service**

1416 & 1800

Rear steering: Increases maneuverability and makes it easier to handle in tight or square headlands and to return on adjacent windrows

Ground clearance: Oxbo mergers provide the ground clearance you need to operate in rough or hilly conditions and to get in and out of the field

Simple folding: Folds to 14ft 2in for easy transport between fields

Multi-stage lift: Oxbo twin mergers provide several stages of lift for easy field navigation. The first lift stage raises the pickup assembly off the ground to raise the tines in severely uneven ground conditions. The second stage raises the conveyor assembly, maintaining a horizontal position. The third lift stage raises the entire pickup/conveyor assembly, arching toward its fully folded position

Customize for your conditions: Available with 4 or 5 foot belt extensions. Merge 9 to 12 foot swath with the extension folded up; merge 13 to 18 foot swaths with the 4 foot extension; 18 to 21 foot swaths with the 5 foot extension

918

Large pick up head: 9ft 6in pickup head with rubber mounted tines and poly tine guards with working widths from 9 to 12 feet

Convenient tension adjustment: Adjust belt tension without tools! Loosen for quick cleaning and easy tension release for storage

Switch hitch: Position the merger directly behind the tractor or off the left side to fit your field and your preferences

Wide product conveyor: The forward tilted 35-inch conveyor provides gentle handling and smooth crop transition from the pickup to the conveyor. Can handle large, heavy crop volume and provides excellent belt tracking



Versatility: Merge to the left, right, or center with the dual pickup configuration

Wide pickup heads: The 7.5 ft pickup heads can be easily adjusted to be centered on 14-, 15-, or 16-foot windrow configurations; and hydraulic width adjustment is optional. The model 1800 features an 18-foot fixed configuration

Even weight distribution: Weight is distributed almost equally between the tractor and the transport wheels spreading the weight over 16 wheels for a smooth ride, low compaction, and fewer ruts, even in soft ground conditions

